



CAUTION!
HIGH VOLTAGE PRESENT ON PANEL
RISK OF ELECTRICAL SHOCK

<p>THE INFORMATION CONTAINED ON THIS DRAWING IS BELIEVED TO BE ACCURATE IN ALL RESPECTS. HOWEVER, TREEHAVEN TECHNOLOGIES, INCORPORATED CANNOT ASSUME RESPONSIBILITY FOR ANY CONSEQUENCES RESULTING FROM THE USE THEREOF. THE INFORMATION CONTAINED HEREIN IS SUBJECT TO CHANGE WITHOUT NOTICE. REVISIONS OR NEW EDITIONS OF THIS DRAWING MAY BE ISSUED TO INCORPORATE SUCH CHANGES</p>		<p>TREEHAVEN TECHNOLOGIES, INC. 24 VILLAGE POINTE DRIVE POWELL, OH 43065 PHONE: 614.791.8843 FAX: 614.789.0252</p>	
<p>NOTES:</p> <ul style="list-style-type: none"> • AC INPUT VOLTAGE: 120VAC, 50/60 HZ, 1.6A • DOME POWER: 24VAC, 50/60HZ, 1.25A • HEATER POWER: 24VAC, 50/60HZ, 5A • CONNECT GROUND TO A GOOD EARTH GROUND 	<p>THE INSTALLATION, FIELD BOX, 120VAC WITH STANDARD SURGE SUPPRESSION, 120VAC TO 24VAC DOME AND HEATER</p>	<p>Size B</p>	<p>Number RVS.FB.120X2</p>
<p>0.25" Typ #10 Clearance</p>	<p>0.25" 0.31" 6.88" 6.26"</p>	<p>8.75" 2.5"</p>	<p>Rev 2</p>
<p>120VAC Power Input (12AWG MAX)</p>	<p>2.63"</p>	<p>Date 5/25/07</p>	<p>Drawn by SVC</p>